



SlideDriver™



Slide Gate Operator

Premium industrial slide gate operator

- Decades long life and low maintenance
- Move the longest, heaviest gates up to 20,000 lb
- Secure, heavy duty chassis - no visible moving parts
- Dual gate, sally port or sequenced gate integration
- Easy system troubleshooting with online events log
- Field programmable to specific site requirements
- UPS models retain full functionality during an AC power outage
- Extreme temperature latitude
- Real time system security alerts
- 5 year warranty



SlideDriver 15
1,500 lb gates
(680 kg)
1 ft/s (30 cm/s)



SlideDriver 30F
3,000 lb gates
(1,361 kg)
1.7 ft/s (50 cm/s)



SlideDriver 40
4,000 lb gates
(1,814 kg)
1 ft/s (30 cm/s)



SlideDriver 50VF 2/3
5,000 lb gates (2,268 kg)
Field adjustable 2.2 or
3 ft/s (70 or 90 cm/s) +
Emergency Fast Close



SlideDriver 80
8,000 lb gates
(3,629 kg)
1 ft/s (30 cm/s)



SlideDriver 200
20,000 lb gates
(9,072kg)
1 ft/s (30 cm/s)



UPS Backup



Sequenced gate



Corrections

Industrial and High Security



Slide Gate Operator

HySecurity operators secure the world's critical infrastructure and key assets where ultimate reliability is vital. SlideDriver delivers uncompromising quality to industrial customers worldwide, where ease of use, consistent operation, low maintenance, long life and high reliability is expected.

31 SlideDriver™ Models

	FAST		FAST			
	1,500 lb (680 kg) gates 1 ft/s (30 cm/s)	3,000 lb (1,361 kg) gates 1.7 ft/s (50 cm/s)	4,000 lb (1,814 kg) gates 1 ft/s (30 cm/s)	5,000 lb (2,268 kg) gates 2.2 ft/s (70 cm/s) or 3 ft/s (91 cm/s)	8,000 lb (3,629 kg) gates 1 ft/s (30 cm/s)	20,000 lb (9,072 kg) gates 1 ft/s (30 cm/s)
Model	SlideDriver 15	SlideDriver 30F	SlideDriver 40	SlideDriver 50VF2/3	SlideDriver 80	SlideDriver 200
Part #	222 SS ST	222 EX 1.7 ST	222 E ST	222 X3 ST	222 X1 ST	444 XS ST
Duty Cycle	Continuous					
Horsepower	1 hp	2 hp	1 hp	2 hp	2 hp	5 hp
Drive	Hydraulic					
Drive Wheels	Two 6" (15 cm) AdvanceDrive wheels	Two 6" (15 cm) AdvanceDrive wheels	Two 6" (15 cm) AdvanceDrive wheels	Two 8" (20 cm) AdvanceDrive wheels	One 8" (20 cm) AdvanceDrive wheel, One 8" XtremeDrive wheel and 27 ft (8 m) of rack	Two 8" (20 cm) AdvanceDrive wheels, Two 8" XtremeDrive wheels and 52 ft (16 m) of rack
Gate Weight Max.	1,500 lb (680 kg)	3,000 lb (1,361 kg)	4,000 lb (1,814 kg)	5,000 lb (2,268 kg)	8,000 lb (3,629 kg)	20,000 lb (9,072 kg)
Gate Length Max.	Limited only by weight					
Drawbar Pull	300 lb (136 kg)	300 lb (136 kg)	300 lb (136 kg)	300 lb (136 kg)	600 lb (272 kg)	1,200 lb (544 kg)
Rate of Travel	1 ft/s (30 cm/s)	1.7 ft/s (50 cm/s)	1 ft/s (30 cm/s)	Field adjustable, 2.2 ft/s (70 cm/s) or 3 ft/s (91 cm/s) Emergency Fast Close 3 ft/s (91 cm/s)	1 ft/s (30 cm/s)	1 ft/s (30 cm/s)
Temperature Rating	-40° F to 158° F (-40° C to 70° C) No heater necessary					
1 Phase Power	115/208/230V 60 Hz 110/220V 50 Hz	208/230V 60 Hz 220V 50 Hz	115/208/230V 60 Hz 110/220V 50 Hz	208/230V 60 Hz 220V 50 Hz	208/230V 60 Hz 220V 50 Hz	230V 60 Hz 220V 50 Hz
3 Phase Power	208/230/460V or 575V 60Hz; 220/380/440V 50Hz			208/230V 60/50Hz or 380/460V 60/50Hz	208/230/460V or 575V 60Hz; 220/380/440V 50Hz	
Communication	RS-232, RS-485, Ethernet/fiber using optional HyNet™ Gateway accessory					
User Controls	Smart Touch Controller with 70+ configurable settings. Smart Touch keypad and display or a PC using S.T.A.R.T. software.					
Relays	Three configurable user relays: one 30VDC, 3A solid state and two 250VAC, 10A electromechanical; Optional Hy8Relay™ for 8 additional relay outputs					
Finish	Zinc plated with powder coating					
Listed to UL325	Usage Class I, II, III, IV	Usage Class III, IV	Usage Class I, II, III, IV	Usage Class III, IV	Usage Class III, IV	Usage Class III, IV
Warranty	5 year					

UPS Backup Power Options and Additional Models

DC Power Supply*	SlideDriver 15 UPS	SlideDriver 30F UPS	SlideDriver 40 UPS	-	SlideDriver 80 UPS	SlideDriver 200 UPS**
AC Power Supply with HyInverter*	SlideDriver 15 with HyInverter	-	SlideDriver 40 with HyInverter	SlideDriver 50VF2/3 with HyInverter	-	-
Correctional Facility	-	SlideDriver 30F-C	SlideDriver 40-C	SlideDriver 50VF2/3-C	SlideDriver 80-C	SlideDriver 200-C
Modular	SlideDriver 15-M	SlideDriver 30F-M	SlideDriver 40-M	SlideDriver 50VF2/3-M	SlideDriver 80-M	SlideDriver 200-M

* 3,000 ft/hr expected duty cycle. ** 2,000 ft/hr expected duty cycle. Actual duty cycle depends on site specific conditions and gate configuration.

To enable fully automatic operation, this gate operator requires a MINIMUM of one external entrapment protection sensor to monitor potential entrapment zones in either the open or close direction of travel. Visit www.hysecurity.com/gatesafety for more information on UL 325 standards and gate safety.

OPTIONAL ACCESSORIES: HY-5A intelligent vehicle detectors, 12 in (30 cm) base extension, tamper proof heavy gauge cover, cabinet lock, solenoid lock, Fire and Emergency Access Lock Box, heater, strobe light, photo eye, snowbrush and scraper kit, XtremeDrive rack kit, custom colors and more.

SYSTEM DESIGN SUPPORT: Contact HySecurity for CAD drawings, tech manuals, help with custom site requirements or other specifications support. Call to speak with a HySecurity representative today.

VISIT WWW.HYSECURITY.COM for specifications, installation manuals, wiring diagrams, parts diagrams, image gallery, videos, training and much more.

Distributed by:



Contact Nice/HySecurity Regional Sales Manager for an operator/parts distributor near you.
 phone 253-867-3700 | 800-321-9947 | www.hysecurity.com | orders@hysecurity.com
 phone 210-545-2900 | 800-226-0178 | www.niceforyou.us | orders@niceforyou.com

